

# Save image on server from external URL

The code presented in this page can be used to save / copy images on server from external URL address, with PHP.

*- Important: If you work on Linux system, PHP must have CHMOD write permissions in the directory in which the image file will be saved.*

```
<?php
// function to get content from a URL address, with cURL
// returns the content of the page with the address passed to $url parameter
function getContentUrl($url) {
    // From: http://coursesweb.net/php-mysql/
    // Setting options for cURL
    $ch = curl_init($url);
    curl_setopt($ch, CURLOPT_RETURNTRANSFER, 1);
    curl_setopt($ch, CURLOPT_BINARYTRANSFER, 1);
    curl_setopt($ch, CURLOPT_USERAGENT, 'Mozilla/21.0 (compatible; MSIE 8.01; Windows NT 5.0)');
    curl_setopt($ch, CURLOPT_TIMEOUT, 200);
    curl_setopt($ch, CURLOPT_AUTOREFERER, false);
    curl_setopt($ch, CURLOPT_REFERER, 'http://google.com');
    curl_setopt($ch, CURLOPT_HTTP_VERSION, CURL_HTTP_VERSION_1_1);
    curl_setopt($ch, CURLOPT_HEADER, 0);
    curl_setopt($ch, CURLOPT_FOLLOWLOCATION, TRUE);    // Follows redirect responses

    // gets the file content, trigger error if false
    $file = curl_exec($ch);
    if($file === false) trigger_error(curl_error($ch));

    curl_close ($ch);
    return $file;
}

$src = 'http://www.marplo.net/imgs/webcourses.gif';    // Image address
$dirimg = 'imgs/';    // directory in which the image will be saved
$localfile = $dirimg . basename($src);    // set image name the same as the file name of the source

// create the file with the image on the server
file_put_contents($localfile, getContentUrl($src));

// Test, show the saved image
echo '<img src="'. $localfile .'>';
?>
```

If the image file already exists on server, in the directory from \$dirimg, the file will be replaced with the new image.

If you want to not replace the old file, but to save the image with another name, replace this line:

**file\_put\_contents(\$localfile, getContentUrl(\$src));**

With this code:

```
// receives the file address, passed by reference
function setLocalfile(&$localfile) {
    GLOBAL $dirimg;
    $imgnm = basename($localfile);    // gets the file name
    preg_match('/^[0-9]*i', $imgnm, $nring);    // gets the number from beginning of file name
    if($nring[0] === '') $imgnm = '0_'. $imgnm;    // if no number, sets 0
    else $imgnm = str_replace($nring[0], $nring[0] + 1, $imgnm);    // replace the number with next one
```

```
$localfile = $dirimg. $imgnm;           // sets the new name, passed by reference to
$localfile
    if(file_exists($dirimg. $imgnm)) setLocalfile($localfile);           // calls the
function to set another name
}

// if the file exists in $dirimg, calls setLocalfile() to set a new file name
if(file_exists($localfile)) setLocalfile($localfile);

// create the file with the image on the server
file_put_contents($localfile, getContentUrl($src));
```

- This code, the setLocalfile() function sets a new name with a consecutive number at the beginning of the file name (image.png, 0\_image.png, 1\_image.png, ...).

- *The getContentUrl() can also be used to get the page content of an URL address.*